SECTION 2.04(E) SCHEDULE: AREA AND BULK REGULATIONS: PARKING REQUIREMENTS

	A	В	MINIMUM LOT SIZE			MINIMUM YARD DIMENSIONS								ACCESSORY BUILDING USES IF DETACHED, MINIMUM DISTANCE TO – (1)					R		S	Т
			С	D	E	F	G	<u>H</u>			J	K	L	M	N	0	Р	Q				
	ZONING DISTRICT	MAXIMUM NUMBER OF DWELLING UNITS	MINIMUM AREA IN SQUARE FEET OR ACRES	WIDTH AT BUILDING LINE, IN LINEAR FEET	MEAN DEPTH IN LINEAR FEET	DEPTH OF FRONT YARD IN I INFAR FEET	DEPTH OF SIDE YARD ABUTING A STREET IN LINEAR FEET	DEPTH OF SIDE YARD ABUTTING A LOT, IN LINEAR FEET		MINIMUM DISTANCE TO NEAREST PRINCIPAL BUILDING ON ADJACENT LOT, IN	DEPTH OF REAR YARD IN LINEAR FEET	MAXIMUM COVERAGE, IN PERCENTAGE OF LOT	FLOOR AREA RATIO	PRINCIPAL BUILDING IN LINEAR FEET	FRONT LOT LINE IN LINEAR FEET	SIDE LOT LINE ADJACENT TO STREET IN LINEAR FEET	OTHER SIDE LOT LINE, IN LINEAR FEET	REAR LOT LINE IN LINEAR FEET	OFF -	NIMUM - STREET NG SPACE	OTHER PROVISIONS AND REQUIREMENTS	MAXIMUM HEIGHT FOR ANY STRUCTURE OR BUILDING
								TOTAL FOR BOTH	MIN. FOR EITHER			(2)	(4)	(5,6)	(5,6)				FOR	ONE SPACE FOR EACH		
1	"SR 1" SINGLE FAMILY RESIDENCE	1 PER 10,000 SQ. FT. OF LOT AREA	10,000 SQ. FT.	80 FT. MIN.	100 FT. MIN.	25 FT. MIN.	25 FT. MIN.	25 FT.	10 FT.	20 FT.	25 FT.	20%		10 FT.	60 FT.	25 FT.	3 FT.	3 FT.	ONE FAMILY DWELLINGS CHURCHES AND	DWELLING UNIT	(1): ANY ATTACHED ACCESSORY BUILDING SHALL BE CONSIDERED AS A PART OF	
2	"SR → 2" SINGLE FAMILY	1 PER 6,000 SQ. FT. OF	6,000 SQ. FT.	50 FT. MIN.	100 FT. MIN.	25 FT. MIN.	15 FT. MIN.	15 FT.	5 FT.	10 FT.	25 FT.	30%	!	10 FT.	60 FT.	25 FT.	3 FT.	3 FT.	AUDITORIUMS LIBRARIES AND		THE PRINCIPAL BUILDING (2): COVERAGE REGULATIONS	
	RESIDENCE "SR - 3"	1 PER 4,000 SQ.	4,000	40 FT.	100 FT.	10 FT.	15 FT.		_		<u> </u>							3 FT.	MUSEUMS MUNICIPAL BUILDINGS	FLOOR AREA 300 SQ. FT. TOTAL FLOOR AREA	DO NOT APPLY TO AUTOMOBILE PARKING AREAS.	THE MAXIMUM HEIGHT FOR ANY STRUCTURE OR BUILDING SHALL BE
3	SINGLE FAMILY RESIDENCE	FT. OF LOT AREA	SQ. FT.	MIN.	MIN.	MIN.	MIN	15 FT.	5 FT.	10 FT.	25 FT.	40%		10 FT.	60 FT.	25 FT.	3 FT.	361.	ELEMENTARY AND JUNIOR	500 SQ. FT. OF	(3): RESIDENTIAL USES ESTABLISHED IN THE "B-1" DISTRICT SHALL COMPLY WITH	THIRTY-FIVE (35) FEET; AND THE MAXIMUM HEIGHT FOR ANY ACCESSORY BUILDING
4	"TR 1" SINGLE FAMILY & MANUFACTURED HOMES RESIDENCE	1 PER 6,000 SQ. FT. OF LOT AREA	6,000 SQ. FT.	50 FT. MIN.	100 FT. MiN.	25 FT. MIN.	25 FT. MIN.	15 FT.	5 FT.	10 FT.	25 FT.	30%		10 FT.	60 FT.	25 FT.	3 FT.	3 FT.	SENIOR HIGH SCHOOLS	200 SQ, FT. OF CLASSROOM AREA	ALL THE REGULATIONS OF THE LEAST RESTRICTIVE RESIDENTIAL DISTRICT IN WHICH THAT TYPE OF RESIDENTIAL USE IS PERMITTED.	SHALL BE FIFTEEN (15) FEET.
5	"MR → 1" TWO OR THREE FAMILY RESIDENCE	1 PER 3,000 SQ. FT. OF LOT AREA	6,000 SQ. FT. Min. OR 3,000 SQ. FT. PER DWELLING UNIT, WHICH EVER IS GREATER	50 FT. MIN. OR 25 FT. FOR EACH DWELLING UNIT OVER 2, WHICH EVER IS GREATER	100 FT. MIN.	25 FT. MIN.	25FT. MIN.	15 FT.	5 FT.	10 FT.	25 FT.	30%		10 FT.	60 FT.	25 FT.	3 FT.	3 FT.	ALL USES PERMITTED BY REFERENCE 2 FAMILY DWELLINGS 3 FAMILY DWELLINGS	SAME AS "SR" DISTRICT .5 DWELLING UNIT .5 DWELLING UNIT	(4): FLOOR AREA RATIO SHALL APPLY TO THE TOTAL AREA INCLUDED IN THE DEVELOPMENT, EXCEPT STREETS AND OTHER PUBLIC AREAS AND SHALL NOT EXCEED THE RATIO SPECIFIED FOR THE DISTRICT WHERE THE	
6	"MR – 2" MULTI-FAMILY RESIDENCE	1 PER 1,500 SQ. FT. OF LOT AREA	6,000 SQ. FT. MIN., OR 1,500 SQ. FT. PER DWELLING UNIT, WHICHEVER IS GREATER	50 FT. MIN. OR 10 FT. FOR EACH DWELLING UNIT OVER 2, WHICH EVER IS GREATER	100 FT. MIN.	25 FT. MIN.	25FT. MIN.	10 FT. OR 6 INCHES PER FT. OF BUILDING HEIGHT, WHICHEVER IS GREATER	10 FT.	10 FT.	25 FT.	30%	· ¾:1	10 FT.	60 FT.	25 FT.	3 FT.	3 FT.	MULTI-FAMILY DWELLINGS BOARDING AND ROOMING HOUSES, DORMITORIES MOBILE HOME PARKS	.5 DWELLING UNIT 2 BEDS MOBILE HOME SPACE	DEVELOPMENT IS LOCATED: WHERE A PLANNED MULTI-FAMILY DEVELOPMENT IS TO BE ESTABLISHED IN A "B" DISTRICT SUCH HOUSING DEVELOPMENT SHALL BE SUBJECT TO THE DENSITY AND HEIGHT REGULATIONS OF THE "MR-2" DISTRICT. (5): DETACHED CARPORTS MAY	THE MAXIMUM HEIGHT FOR ANY STRUCTURE OR BUILDING SHALL BE NON-APPLICABLE; AND THE MAXIMUM HEIGHT FOR ANY ACCESSORY BUILDING SHALL BE FIFTEEN (15) FEET.
7	"B — 1" COMMUNITY BUSINESS	(3)						NONE REQUIR PROVIDED O ABUTTING AN OR "MR DISTR YARD OF 1: REQUIF	OR WHEN I "SR", "TR" ICT A SIDE 2 FT. IS		20 FT.	50%	2:1	12 FT.	12 FT.	12 FT.	12 FT.	12 FT.			BE EXEMPTED FROM COLUMN "M" AND COLUMN "N" REQUIREMENTS BUT SHALL. NOT BE CLOSER TO THE FRONT LOT LINE THAN THE EXISTING FRONT BUILDING	
8	"B – 2" GENERAL BUSINESS							50 FT.	25 FT.		20 FT.	50%	2;1	12 F⊺.	12 FT.	12 FT.	12 FT.	12 FT.			LINE OF THE PRINCIPAL STRUCTURE. (6)ACCESSORY BUILDINGS SHALL NOT EXTEND TOWARD	
9	"B – 3" HIGHWAY BUSINESS							50 FT.	25 FT.		20 FT.	50%	2:1	12 FT.	(6)	12 FT.	12 FT.	12 FT.			THE FRONT LOT LINE BEYOND THE FRONT WALL OF THE PRINCIPAL BUILDING.	
10	" " INDUSTRIAL					25 FT.	25 FT.	50 FT.	25 FT.		20 FT.	40%	1:1	10 FT.	10 FT.	10 FT.	10 FT.	10 FT.				